

# DP-6200 BENCH/RECEIVING SCALE **Yamato**

## Features

- Stainless Steel Platform
- Over/Under Indicator
- Tilting and Rotating LCD Display with Annunciators
- Push Button Tare
- Battery and AC operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Legal for Trade



Model	DP-6200	DP-6200-C	DP-6200-Z*
Capacity and Divisions	60 lb x 0.02 lb (30 kg x 0.01 kg) 150 lb x 0.05 lb (60 kg x 0.02 kg) 300 lb x 0.1 lb (150 kg x 0.05 kg)	960 oz x 0.5oz (30 kg x 0.01 kg) 2400 oz x 1 oz (60 kg x 0.02 kg) 4800 oz x 2 oz (150 kg x 0.05 kg)	60 lb x 0.5 oz (30 kg x 0.01 kg) 150 lb x 1 oz (60 kg x 0.02 kg) 300 lb x 2 oz (150 kg x 0.05 kg)
Accuracy	Class III, 3000 Divisions		
Certificate of Conformance	03-002A2		
Weighing System	Strain gauge load cell		
Platform	13.8 "W x 19.7" D stainless steel (350W x 500D mm)		
Display	LCD: 5 digits plus annunciators		
Character Size	Character size: 0.9"H x 0.5"W (23H x 12W mm)		
Power	6 "D" batteries		
Battery Life	Alkaline batteries: 600 hours (continuous use)		
Operating Temperatures	23° F ~ 95° F (-5° C ~ 35° C)		
Options	RS-232C serial communications, AC adapter, rechargeable battery pack		

\*Combined units, such as pound-ounce, are not legal for trade.

## Weigh Better Solutions • Weigh Better Support

**Yamato Corporation**  
6306 W. Eastwood Ct.  
Mequon, WI 53092  
Tel: 262.236.0000  
Fax: 262.236.0036

**Yamato Corporation**  
20451 James Bay Circle  
Lake Forest, CA 92630  
Tel: 800.538.1762

**Yamato Scale de Mexico**  
Av. Dr. Gustavo Baz 191, Bodega F  
Col. El Mirador, CP. 54080  
Tlalneantla de Baz, Mexico  
Tel: 52-55-2628-6140

[www.YamatoAmericas.com](http://www.YamatoAmericas.com)

# DP-6200 BASCULA DE PLATAFORMA/ RECEPCIÓN

# Yamato

## Características

- Plataforma de acero inoxidable
- Indicador Más / Menos
- Pantalla LCD giratoria con inclinacion y cuadro indicador
- Botón Tare
- Operación con Batería o AC
- Apagado Auto Ajustable
- Ajustes de mecanismos Zero Inicial, Automatico y Semi-automatico
- Legal para el comercio



Model	DP-6200	DP-6200-C	DP-6200-Z*
Capacidad and Divisiones	60 lb x 0.02 lb (30 kg x 0.01 kg) 150 lb x 0.05 lb (60 kg x 0.02 kg) 300 lb x 0.1 lb (150 kg x 0.05 kg)	960 oz x 0.5oz (30 kg x 0.01 kg) 2400 oz x 1 oz (60 kg x 0.02 kg) 4800 oz x 2 oz (150 kg x 0.05 kg)	60 lb x 0.5 oz (30 kg x 0.01 kg) 150 lb x 1 oz (60 kg x 0.02 kg) 300 lb x 2 oz (150 kg x 0.05 kg)
Precision	Clase III, 3000 divisiones		
Certificado de Conformidad	03-002A2		
Sistema de peso	Celulas de pesaje extensometrico		
Plataforma	13.8 "W x 19.7"D acero inoxidable (350W x 500D mm)		
Pantalla	LCD: 5 digitos más anunciadores		
Tamaño de caracteres	Character size: 0.9"H x 0.5"W (23H x 12W mm)		
Energia	Seis baterias "D"		
Duración de la batería	600 horas de uso continuo con baterías alcalinas		
Temperaturas de funcionamiento	23° F ~ 95° F (-5° C ~ 35° C)		
Opciones	Serie RS-232C de comunicaciones, Adaptador AC, bateria recargable		

\*Unidades combinadas, como libras-onzas, no son legales para el comercio

## Weigh Better Solutions • Weigh Better Support

**Yamato Corporation**  
6306 W. Eastwood Ct.  
Mequon, WI 53092  
Tel: 262.236.0000  
Fax: 262.236.0036

**Yamato Corporation**  
20451 James Bay Circle  
Lake Forest, CA 92630  
Tel: 800.538.1762

**Yamato Scale de Mexico**  
Av. Dr. Gustavo Baz 191, Bodega F  
Col. El Mirador, CP. 54080  
Tlalneantla de Baz, Mexico  
Tel: 52-55-2628-6140

[www.YamatoAmericas.com](http://www.YamatoAmericas.com)

Form No. YSS-DP6200-1115-01