

PPC-200W WASHDOWN PORTION CONTROL SCALE

Yamato

Features

- Legal for Trade
- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Push Button Tare
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- IP65 Washdown¹
- Capacities from 4 lb to 50 lb (2 kg to 20 kg)



	PPC-200W	PPC-200WC	PPC-200WZ*
Capacity and Divisions	4 lb x 0.002 lb (2 kg x 0.001 kg) 10 lb x 0.005 lb (4 kg x 0.002 kg) 20 lb x 0.01 lb (10 kg x 0.005 kg) 40 lb x 0.02 lb (20 kg x 0.01 kg)	80 oz x 0.05oz (2 kg x 0.001 kg) 160 oz x 0.1 oz (4 kg x 0.002 kg) 320 oz x 0.2 oz (10 kg x 0.005 kg) 800 oz x 0.5 oz (20 kg x 0.01 kg)	5 lb x 0.05 oz (2 kg x 0.001 kg) 10 lb x 0.1 oz (4 kg x 0.002 kg) 20 lb x 0.2 oz (10 kg x 0.005 kg) 50 lb x 0.5 oz (20 kg x 0.01 kg)
Accuracy Class	Class III, 2000 divisions		
Certificate of Conformance	98-125A5		
Weighing System	Strain gauge load cell		
Platform	9" x 9" stainless steel, removable (230 x 230 mm)		
Display	LCD: 5 digits plus annunciators		
Character Size	Character Size: 0.9"x 0.5" (22 x 12 mm)		
Housing Material	ABS Plastic		
Power	Six "D" size batteries		
Operating Temperatures	14° F to 104° F (-10° C to 40° C)		
Battery Life	1000 hours of continuous use with alkaline batteries		
Options	RS-232 serial communication AC Adapter		

¹PPC-200W's are not washdown IP65 with AC adaptor installed. *Combined units, such as pound-ounce, are not legal for trade.

Weigh Better Solutions • Weigh Better Support

Yamato Corporation
6306 W. Eastwood Ct.
Mequon, WI 53092
Tel: 262.236.0000
Fax: 262.236.0036

Yamato Corporation
20451 James Bay Circle
Lake Forest, CA 92630
Tel: 800.538.1762

Yamato Scale de Mexico
Av. Dr. Gustavo Baz 191, Bodega F
Col. El Mirador, CP. 54080
Tlalnepantla de Baz, Mexico
Tel: 52-55-2628-6140

www.YamatoAmericas.com

Form No. YSS-PPC200W-1115-01

PPC-200W LAVABLE BASCULA DE CONTROL DE PORCIONES

Yamato

Características

- Legal para el comercio
- Indicador Más / Menos
- Plataforma grande de acero inoxidable desmontable
- Botón Tare
- Pantalla grande LCD
- Operación con Batería o AC
- Apagado Auto Ajustable
- Ajustes de mecanismos Zero Inicial, Automatico y Semi-automatico
- IP65¹ Lavable
- Capacidades desde 4 lb a 50 lb (2 kg to 20 kg)



	PPC-200W	PPC-200WC	PPC-200WZ*
Capacity and Divisions	4 lb x 0.002 lb (2 kg x 0.001 kg) 10 lb x 0.005 lb (4 kg x 0.002 kg) 20 lb x 0.01 lb (10 kg x 0.005 kg) 40 lb x 0.02 lb (20 kg x 0.01 kg)	80 oz x 0.05oz (2 kg x 0.001 kg) 160 oz x 0.1 oz (4 kg x 0.002 kg) 320 oz x 0.2 oz (10 kg x 0.005 kg) 800 oz x 0.5 oz (20 kg x 0.01 kg)	5 lb x 0.05 oz (2 kg x 0.001 kg) 10 lb x 0.1 oz (4 kg x 0.002 kg) 20 lb x 0.2 oz (10 kg x 0.005 kg) 50 lb x 0.5 oz (20 kg x 0.01 kg)
Clase de precision	Clase III, 2000 divisiones		
Certificado de Conformidad	98-125A5		
Sistema de peso	Celulas de pesaje extensometrico		
Plataforma	9" x 9" acero inoxidable, removible (230 x 230 mm)		
Pantalla	LCD: 5 digitos más anunciadores		
Tamaño de caracteres	0.9"x 0.5" (22 x 12 mm)		
Material de la cubierta	Plastico ABS		
Energia	Seis baterias "D"		
Temperaturas de funcionamiento	14° F to 104° F (-10° C to 40° C)		
Duración de la batería	1000 horas de uso continuo con baterias alcalinas		
Opciones	Comunicacion RS-232 Adaptador AC		

¹PPC-200W's no es IP65 lavable con el adaptador AC instalado. *Unidades combinadas, como libras-onzas, no son legales para el comercio.

Weigh Better Solutions • Weigh Better Support

Yamato Corporation
6306 W. Eastwood Ct.
Mequon, WI 53092
Tel: 262.236.0000
Fax: 262.236.0036

Yamato Corporation
20451 James Bay Circle
Lake Forest, CA 92630
Tel: 800.538.1762

Yamato Scale de Mexico
Av. Dr. Gustavo Baz 191, Bodega F
Col. El Mirador, CP. 54080
Tlalnepantla de Baz, Mexico
Tel: 52-55-2628-6140

www.YamatoAmericas.com

Form No. YSS-PPC200W-1115-01