

Features

- **Go Green and save money**
- Solar powered operation (more than 300Lx) or two optional AA batteries
- Long battery life (10,000 hours)
- Over/under function
- Stainless steel construction with removable platform
- Dual range
- Multiple weighing units - lb, g, oz and lb/oz
- Adjustable auto shut-off
- Large easy to read LCD display
- Initial, automatic and semi-automatic zero setting mechanisms



Model	SPC-Solar 2		SPC-Solar 5	
Accuracy	1250 Divisions			
Capacity and Divisions	Low Range 0 - 2.2lb x 0.002lb 0 - 2lb 3oz x 0.05oz 0 - 35oz x 0.05oz 0 - 1000g x 1g	High Range 2.2 - 4.4lb x 0.005lb 2lb 3oz - 4lb 6oz x 0.1oz 35 - 70oz x 0.1oz 1000 - 2000g x 2g	Low Range 0 - 5.5lb x 0.005lb 0 - 5lb 8oz x 0.1oz 0 - 88oz x 0.1oz 0 - 2500g x 2g	High Range 5.5 - 11.0lb x 0.01lb 5lb 8oz - 11lb 2oz x 0.2oz 88 - 178oz x 0.2oz 2500 - 5000g x 5g
Weighing System	Strain gauge load cell			
Platform	6.7"W x 6.3"D stainless steel, removable (170W x 160D mm)			
Display	Liquid crystal display: 5 digits plus annunciators Character size: 0.47"W x 0.83"H (12W x 21H mm)			
Power	Solar power (more than 300Lx) or two optional AA batteries			
Battery Life	Alkaline batteries: 10,000 hours (continuous use)			
Outside Dimensions	7.1"W x 9.5"D x 2.5"H (180W x 240D x 63H mm)			
Operating Temperatures	32° F ~ 104° F (0° C ~ 40° C)			

Weigh Better Solutions • Weigh Better Support

Yamato Corporation
 6306 W. Eastwood Ct.
 Mequon, WI 53092
 Tel: 262.236.0000
 Fax: 262.236.0036

Yamato Corporation
 20451 James Bay Circle
 Lake Forest, CA 92630
 Tel: 800.538.1762

Yamato Scale de Mexico
 Av. Dr. Gustavo Baz 191, Bodega F
 Col. El Mirador, CP. 54080
 Tlalneantla de Baz, Mexico
 Tel: 52-55-2628-6140

www.YamatoAmericas.com

Características

- **Protege el medio ambiente y ahorra dinero**
- Funcionamiento con energía solar (más de 300LX) o dos baterías opcionales AA
- Batería de larga duración (10,000 Horas)
- Función de sobre/bajo peso
- Hecho de acero inoxidable con plataforma extraíble
- Doble rango
- Múltiples unidades de pesaje - lb, g, oz, lb/oz
- Apagado automático ajustable
- Pantalla grande LCD fácil de leer
- Mecanismo de ajuste cero inicial, automático y semiautomático



Modelo	SPC-Solar 2		SPC-Solar 5	
Exactitud	1250 divisiones			
Capacidad y divisiones	Rango bajo 0 - 2.2lb x 0.002lb 0 - 2lb 3oz x 0.05oz 0 - 35oz x 0.05oz 0 - 1000g x 1g	Rango Alto 2.2 - 4.4lb x 0.005lb 2lb 3oz - 4lb 6oz x 0.1oz 35 - 70oz x 0.1oz 1000 - 2000g x 2g	Rango bajo 0 - 5.5lb x 0.005lb 0 - 5lb 8oz x 0.1oz 0 - 88oz x 0.1oz 0 - 2500g x 2g	Rango Alto 5.5 - 11.0lb x 0.01lb 5lb 8oz - 11lb 2oz x 0.2oz 88 - 178oz x 0.2oz 2500 - 5000g x 5g
Sistema de pesaje	Célula de carga de galgas extensométricas			
Plataforma	6.7"W x 6.3"D Acero inoxidable, extraíble (170W x 160D mm)			
Pantalla	Pantalla de cristal líquido LCD: 5 dígitos más anunciadores Tamaño de letra: 0.47"W x 0.83"H (12W x 21H mm)			
Energía	Energía Solar (más de 300LX) o dos baterías AA opcionales			
Duración de la batería	Pilas alcalinas: 10,000 horas (uso continuo)			
Dimensiones Exteriores	7.1"W x 9.5"D x 2.5"H (180W x 240D x 63H mm)			
Temperaturas de funcionamiento	32° F ~ 104° F (0° C ~ 40° C)			

Mejor Soluciones de Pesaje • Mejor Soporte de Pesaje

Yamato Corporation
 6306 W. Eastwood Ct.
 Mequon, WI 53092
 Tel: 262.236.0000
 Fax: 262.236.0036

Yamato Corporation
 20451 James Bay Circle
 Lake Forest, CA 92630
 Tel: 800.538.1762

Yamato Scale de Mexico
 Av. Dr. Gustavo Baz 191, Bodega F
 Col. El Mirador, CP. 54080
 Tlalnepanlta de Baz, Mexico
 Tel: 52-55-2628-6140

www.YamatoAmericas.com