

DP-6700 BENCH/ RECEIVING SCALE

Yamato

Features

- Stainless steel construction
- Functions: checkweighing, grading, packing, counting and weight totals
- Tilting LCD display with annunciators
- Battery and AC/DC operation
- Color LED under/accept/over annunciator
- Adjustable auto shut-off
- Washdown - NEMA 4/IP65 when battery operated and AC jack is sealed
- Initial, automatic and semi-automatic zero setting mechanisms
- Optional USB flash drive



Model	DP-6700-60	DP-6700-150	DP-6700-300
Accuracy	Class III, 3000 Divisions		
Capacity and Divisions	30 kg x 0.01 kg 60 lb x 0.02 lb 960 oz x 0.05 oz 60 lb x 0.05 oz	60 kg x 0.02 kg 150 lb x 0.05 lb 2400 oz x 1 oz 150 lb x 1 oz	150 kg x 0.05 kg 300 lb x 0.1 lb 4800 oz x 2 oz 300 lb x 2 oz
Weighing System	Strain gauge load cell		
Platform	13.7" W x 19.7"D stainless steel (350W x 500D mm)		
Display	Liquid crystal display: 5 digits plus annunciators Character size: 1.8"H x 0.9"W (45H x 23.5W mm)		
Power	4 "D" batteries, optional AC adaptor (not washdown), included		
Battery Life	Alkaline batteries: 1400 hours (continuous use)		
Outside Dimensions	7.1"W x 9.5"D x 2.5"H (180W x 240D x 63H mm)		
Operating Temperatures	14° F ~ 104° F (-10° C ~ 40° C)		
Certificate of Conformance	11-007A1, AM-5816 (Canada)		

Weigh Better Solutions • Weigh Better Support

Yamato Corporation

6306 W. Eastwood Ct.
Mequon, WI 53092
Tel: 262-236-0000
Fax: 262-236-0036

Yamato Corporation

20451 James Bay Circle
Lake Forest, CA 92630
Tel: 949-238-4500
Fax: 949-455-2711

Yamato Scale de Mexico

Av. Dr. Gustavo Baz 191, Bodega F
Col. El Mirador, CP. 54080
Tlalnepantla de Baz, Estado de Mexico
Tel: 52 55 2628-6140

www.YamatoAmericas.com
Form No. YSS-DP6700NSF-0818-01

DP-6700 BASCULA DE MESA/RECEPCIÓN

Yamato

Características

- Construcción de acero inoxidable
- Funciones: Control de peso, clasificación, embalaje, conteo y pesaje totales
- Pantalla inclinada LCD con anunciadores
- Operación con baterías t AC/DC
- Anunciador LED de colores para la opciones por debajo/aceptar/sobre
- Apagado automático ajustable
- Lavable - NEMA 4/IP65 cuando es operada con la batería y el conector AC esta sellado
- Mecanismo de ajuste inicial, automático y semiautomático
- Opcional USB Flash



Modelo	DP-6700-60	DP-6700-150	DP-6700-300
Precisión	Class III, 3000 Divisiones		
Capacidad y Divisiones	30 kg x 0.01 kg 60 lb x 0.02 lb 960 oz x 0.05 oz 60 lb x 0.05 oz	60 kg x 0.02 kg 150 lb x 0.05 lb 2400 oz x 1 oz 150 lb x 1 oz	150 kg x 0.05 kg 300 lb x 0.1 lb 4800 oz x 2 oz 300 lb x 2 oz
Sistema de pesaje	Células de carga de galgas extenso		
Plataforma	13.7" W x 19.7"D Acero inoxidable (350W x 500D mm)		
Pantalla	Pantalla con líquido de cristal: 5 dígitos más anunciadores Tamaño de la letra: 1.8"H x 0.9"W (45H x 23.5W mm)		
Energía	4 "D" Baterías, adaptador AC opcional (no lavable)		
Duración de la batería	Baterías alcalinas: 1400 horas (uso continuo)		
Dimensiones exteriores	7.1"W x 9.5"D x 2.5"H (180W x 240D x 63H mm)		
Temperaturas de funcionamiento	14° F ~ 104° F (-10° C ~ 40° C)		
Certificado de conformidad	11-007A1, AM-5816 (Canada)		

Weigh Better Solutions • Weigh Better Support

Yamato Corporation

6306 W. Eastwood Ct.
Mequon, WI 53092
Tel: 262-236-0000
Fax: 262-236-0036

Yamato Corporation

20451 James Bay Circle
Lake Forest, CA 92630
Tel: 949-238-4500
Fax: 949-455-2711

Yamato Scale de Mexico

Av. Dr. Gustavo Baz 191, Bodega F
Col. El Mirador, CP. 54080
Tlalnepantla de Baz, Estado de Mexico
Tel: 52 55 2628-6140

www.YamatoAmericas.com
Form No. YSS-DP6700NSF-0818-01