

DP-6700 Standard Series Bench/Receiving Scales

- IP65 washdown
- · Stainless-steel construction
- · Pound, ounce, kilogram, pound-ounce
- · Programmable auto-off
- · Checkweighing, grading, packing, counting, and basic weighing






Large, easy-toread LCD display characters


WEGITE OF THE PROPERTY OF THE	Color LED under/accept/over annunciator
	13.8in x 19.7in stainless-steel platform


MODEL	DP-6700-60	DP-6700-150	DP-6700-300
Capacity	60lb x 0.02lb 960oz x 0.5oz 30kg x 0.01kg 60lb x 0.5oz*	150lb x 0.05lb 2400oz x 1oz 60kg x 0.02kg 150lb x 1oz*	300lb x 0.1lb 4800oz x 2oz 150kg x 0.05kg 300lb x 2oz*
Weighing System	Strain gauge load cell		
Certificate of Conformance	11-007A1 (US); AM-5816 (Canada)		
Platform	13.8in x 19.7in (350mm x 500mm) stainless steel		
Display	5-digit, 7-segment LCD plus annunciators		
Character Size	1.8in x 0.9in (45mm x 23mm)		
Power	"D" size batteries (qty. 4) or AC adapter (included)		
Battery Life	1400 hours of continuous use		
Housing Material	Stainless Steel		
Operating Temperatures	14°F ~ 104°F (-10°C ~ 40°C)		
Functions	Basic weighing, checkweighing, grading, packing, counting, tare		
Power Battery Life Housing Material Operating Temperatures	"D" size batteries (qty. 4) or AC adapter (included) 1400 hours of continuous use Stainless Steel 14°F ~ 104°F (-10°C ~ 40°C)		

^{*}Combined units, such as pound-ounce, are not legal for trade.

Dimensions







YamatoAmericas.com

