

### DP-6900 Series Bench/Receiving Scales

- Pound, kilogram, ounce, pound-ounce
- Rechargeable battery and AC operation
- Checkweighing, gross/net weighing, and basic weighing
- Programmable auto-off
- RS-232 option
- LED checkweighing over/under indicator



MODEL	DP-6900-60	DP-6900-150	DP-6900-300
Capacity	60lb x 0.02lb 960oz x 0.5oz 30kg x 0.01kg 60lb x 0.5oz*	150lb x 0.05lb 2400oz x 1oz 60kg x 0.02kg 150lb x 1.0oz*	300lb x 0.1lb 4800oz x 2oz 150kg x 0.05kg 300lb x 2.0oz*
Weighing System	Strain gauge load cell		
Certificate of Conformance	17-019 (US); AM-6052 (Canada)		
Platform	13.8in x 19.7in (350mm x 500mm) stainless steel, removable		
Display	5-digit, 7-segment LCD plus annunciators		
Character Size	1.3in x 0.7in (32mm x 17mm)		
Power	Rechargeable battery or AC adapter (included)		
Battery Life	240 hours of continuous use Charging time: Approximately 12 hours		
Housing Material	ABS indicator with stainless-steel base		
Operating Temperatures	14°F ~ 104°F ( -10°C ~ 40°C)		
Functions	Basic weighing, tare, checkweighing, gross/net weighing		
Options	RS-232C serial output, alkaline battery pack		

\*Combined units, such as pound-ounce, are not legal for trade.

Tilting and rotating indicator

Large, easy-to-read LCD Display

Removable stainless-steel platform



### Dimensions

